

A STRONG DUO FOR WALLS

Screws and plugs – certainly, of course from SPAX.





NEW



THE SPAX PLUG FOR RELIABLE INSTALLATION

The new SPAX plug Type SD: A perfect installation result thanks to the ideal combination of SPAX screw and SPAX expansion plug.

Special features

- Optimally matched to SPAX screws for simple fastening, even by hand.
- Perfect clamping in connection with SPAX partial thread screws.
- Special 4-way expansion: guarantees optimal force distribution and ensures a strong hold in the building material.
- High-quality nylon: makes the plug particularly sturdy, durable and highly resilient. Can also be used outdoors with stainless-steel screws.

Versatile



Concrete



Solid bricks



Ventilating
Aerated bricks



concrete



PERFECTION IN DETAIL

T-STAR plus drive

Optimal force transmission

Special geometry

Perfectly matched screw and plug

Plug collar

Prevents plug from slipping into the drill hole

Expansion-free plug neck

Prevents damage, for instance, to tiles

4-way expansion

Provides the optimum force distribution and high load-bearing capacities

Anti-rotation locks


Prevent plug from rotating in the drill hole

Nylon

Ultra-stable, highly resilient and weatherproof







Minimum screw length = attachment part + plug length + 5 mm

Combi packs (screw + plug)												
mm	Ø mm	A	B	C	D	kg	kg	kg	kg			
5 _× 25	3,5 x 35	5	≥40	≥30	≤5	20	21	10	1			
6×30	4,5 x 45	6	≥50	≥35	≤10	37	33	14	3			
6.45	4,5 x 60	6	≥65	≥50	≤10	42	55	12	6			
8.40	5 _x 60	8	≥65	≥45	≤15	27	29	13	7			

Mono packs (plug only)												
	£	Attachment part thickness										
Tributing .		5 mm	10 mm	15 mm	20 mm	25 mm						
mm	Ø mm	Recommended SPAX dimensions										
5 _× 25	3-4	3.5×35	3.5×40	3.5 x 45	3.5×50	4×60						
6×30	4-5	4.5×40	4.5×45	4.5×50	4.5×60	4.5×70						
6×45	4-5	4.5×60	4.5×70	4.5×70	4.5×80	4.5×80						
8,40	4,5-6	5×50	5×60	5×60	5×70	5×80						

SPAX International GmbH & Co. KG

ALTENLOH, BRINCK & CO - GRUPPE SEIT 1823

Kölner Straße 71–77 · 58256 Ennepetal · Germany Tel.: +49-23 33-799-1967 · Fax: +49-23 33-799-199

info@spax.com · www.spax.com

You'll also find us at:

facebook.com/spax

instagram.com/spax_international youtube.com/user/SPAXinternational linkedin.com/company/spax-international SPAX article number 6126

